

10/534356

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



534 356

(43) International Publication Date  
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number  
WO 2004/051181 A1

(51) International Patent Classification: G01B 7/012

(21) International Application Number:  
PCT/GB2003/005317

(22) International Filing Date: 5 December 2003 (05.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0228368.7 5 December 2002 (05.12.2002) GB

(71) Applicant (for all designated States except US): REN-  
ISHAW plc [GB/GB]; New Mills, Wotton-under-Edge,  
Gloucestershire GL12 8JR (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): McMURTRY,

David, Roberts [GB/GB]; Park Farm, Stancombe, Durs-  
ley, Gloucestershire GL11 6AT (GB). McFARLAND,  
Geoffrey [GB/GB]; The Manse, 22 Church Road, Upper  
Cam, Dursley, Gloucestershire GL11 5PG (GB).


(74) Agent: JACKSON, John, Timothy et al; Renishaw  
plc, Patent Department, New Mills, Wotton-under-Edge,  
Gloucestershire GL12 8JR (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,  
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,  
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,  
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: PROBE FOR HIGH SPEED SCANNING



(57) Abstract: A measurement probe (5) which comprises a housing (16) for mounting on an arm (6) of a coordinate positioning apparatus (2) and a stylus (10) mounted on a stylus support member (28). The stylus (10) and the stylus support member (28) are deflectable with respect to the housing (16). A first transducer system (40-48) measures movement of the stylus support member (28) relative to the arm (6) of the coordinate positioning apparatus (2). A second transducer system (38) measures movement of the stylus tip (12) relative to the stylus supporting member (28). A measurement of total stylus deflection is achieved by combining data from the first and second transducer systems.

WO 2004/051181 A1